

GREASE MF (EP) 2

Multifunctional EP Grease

Piston Power Grease MF (EP) 2 is a multi-functional, lithium soap base grease containing extreme pressure additives, and rust and oxidation inhibitors.

Applications

Suitable for use in the following applications:

- Automotive
- Construction equipment
- Earthmoving, quarrying and mining
- Agricultural equipment
- Industrial equipment

Grease MP (EP) 2 can be used to lubricate the following components:

- Wheel bearings
- Water pumps
- Motor bearings
- Plain and rolling element bearings
- Chassis grease points

Performance Features

- Operating temperature range of -30°C to +120°C.
- Lessens maintenance costs. Effective EP additive protects against component wears under high load conditions.
- Reduces downtime. Excellent oxidation resistance ensures longer grease life.
- Rationalisation of grease types. Multi-functional capability allows use in a wide range of automotive and industrial applications and eliminating product misapplication.
- Good pumpability characteristics of the lithium thickener provide suitable flow characteristics for grease pump application systems.
- Excellent resistance to water wash out. This ensures that bearings operating in

wet conditions are protected against breakdown due to rust.

Performance Specifications

Piston Power Grease MF (EP) 2 meets the following performance specifications:

SANS 1851:2021

Typical Characteristics

Thickener	Lithium
NLGI Consistency	2
Colour	Amber
Structure	Smooth
Worked Penetration @ 25°C 0.1mm (ASTM D217)	280
Dropping Point °C (ASTM D2265)	185
Timken OK Load kg (ASTM D2509)	25
Base Oil Kinematic Viscosity mm ² /s At 40°C (ASTM D445)	220